



PILA LED Waterproof

Benefits

- Solid fixture
- Available in three sizes
- Supports energy saving

80

CRI

35.000 h

220-240 Vac

II

Protection class

IP65

IP rating

IK08

IK rating

TW

Through wiring available

Product type

	LED (W)	CCT (K)	Luminous flux (lm)	Power factor	Voltage frequency	EAN1	12NC
PILA WT008C 20S/840 PSU L600 CLASSIC	18	4000	2000	> 0.9	50-60Hz	8719514964907	911401813685
PILA WT008C 40S/840 PSU L1200 CLASSIC	36	4000	4000	> 0.9	50-60Hz	8719514964914	911401813785
PILA WT008C 60S/840 PSU L1500 CLASSIC	53	4000	6000	> 0.9	50-60Hz	8719514964921	911401813885
PILA WT008C 20S/840 PSU L600 TW CLASSIC	18	4000	2000	> 0.9	50-60Hz	8719514964938	911401813985
PILA WT008C 40S/840 PSU L1200 TW CLASSIC	36	4000	4000	> 0.9	50-60Hz	8719514964945	911401814085
PILA WT008C 60S/840 PSU L1500 TW CLASSIC	53	4000	6000	> 0.9	50-60Hz	8719514964952	911401814185

