

PHILIPS

Compatibility List Professional Q2 2026 TrueForce LED HID

Table of contents

| | |
|---|-----------------------|
| TrueForce LED HPI - Universal | 2 |
| MASTER LED SON-T - InstantFit | 3 - 4 |
| MASTER LED SON - T - EM/Mains Voltage | 5 |
| MASTER LED SON-T Ultra Efficient - Mains | 6 |
| TrueForce Core LED SON-T - Mains Voltage | 7 |
| TrueForce LED HPL - EM/Mains | 8 |
| MASTER LED HPL - Mains | 9 |
| TrueForce CorePro LED HPL - Mains Voltage | 10 |

Key

This document is for information purposes and must be treated as recommendation. Signify attempts to provide accurate result which are generated in lab conditions and might not completely reflect actual conditions.

[illegible][Installer Hub | Philips lighting](#)

MASTER LED SON-T - InstantFit

| | | |
|------------|--------------------------------------|---|
| 9290034670 | MAS LED SON-T IF 3.6Klm 23W 727 E27 |  |
| 9290034671 | MAS LED SON-T IF 4Klm 23W 740 E27 | |
| 9290034672 | MAS LED SON-T IF 5.4Klm 34W 727 E27 | |
| 9290034673 | MAS LED SON-T IF 6Klm 34W 740 E27 | |
| 9290034674 | MAS LED SON-T IF 8.1Klm 50W 727 E40 | |
| 9290034675 | MAS LED SON-T IF 9Klm 50W 740 E40 | |
| 9290034676 | MAS LED SON-T IF 10.8Klm 65W 727 E40 | |
| 9290034677 | MAS LED SON-T IF 12Klm 65W 740 E40 | |

Ballast - Igniter compatibility list

| | | |
|------|----------------------------|---|
| Key | | <i>This document is for information purposes and must be treated as recommendation. Signify attempts to provide accurate result which are generated in lab conditions and might not completely reflect actual conditions.</i> |
| | Compatible. | |
| | Limited compatibility | |
| | Not Compatible | |
| N.A. | Combination not applicable | |

| EM ballast type | EM ballast Brand | MAS LED SON-T IF 3.6Klm 23W E27 | MAS LED SON-T IF 5.4Klm 34W E27 | MAS LED SON-T IF 8.1Klm 50W E40 | MAS LED SON-T IF 10.8Klm 65W E40 |
|------------------------------|------------------|--|--|--|--|
| | | Model Number/(Short) EOC wcode 9290034670/871951444887200 9290034671/871951444889600 | Model Number/(Short) EOC wcode 9290034672/871951444891900 9290034673/871951444893300 | Model Number/(Short) EOC wcode 9290034674/871951444895700 9290034675/871951444897100 | Model Number/(Short) EOC wcode 9290034676/871951444899500 9290034677/871951444901500 |
| BSN 50W | PHILIPS | | | | |
| BSN 70W | PHILIPS | | | | |
| BHL 80W | PHILIPS | | | | |
| BHL 125W | PHILIPS | | | | |
| BSN 100W | PHILIPS | | | | |
| BSN 150W | PHILIPS | | | | |
| NK70/50LUP | Helvar | | | | |
| NG70ZT | OSRAM | | | | |
| VS PKNaHJ 70.128 | Vossloh Schwabe | | | | |
| 70W 1.0A MH/HPS HSA07223221 | PARMAR | | | | |
| 100W 1.2A MH/HPS HSP10223221 | PARMAR | | | | |
| NaHJ 100.581 | Vossloh Schwabe | | | | |
| 150W 1.8A MH/HPS HSA15223221 | PARMAR | | | | |
| NaHJ 150.995 | Vossloh Schwabe | | | | |
| NK 150 SEP | Helvar | | | | |
| BSD 100L 406TS | PHILIPS | | | | |
| BSD 150L 406TS | PHILIPS | | | | |

The product is compatible with BSN and BHL ballast (or similar models from other suppliers), see above table.
The product is NOT compatible with electronic ballasts
The product is NOT compatible with CWA type of ballasts/transformers

| BSN-series ballast type (or similar) combined with following igniter | | | | MAS LED SON-T IF 3.6Klm 23W E27 | MAS LED SON-T IF 5.4Klm 34W E27 | MAS LED SON-T IF 8.1Klm 50W E40 | MAS LED SON-T IF 10.8Klm 65W E40 |
|--|---------------|--|---------------|--|--|--|--|
| | | | | Model Number/(Short) EOC wcode 9290034670/871951444887200 9290034671/871951444889600 | Model Number/(Short) EOC wcode 9290034672/871951444891900 9290034673/871951444893300 | Model Number/(Short) EOC wcode 9290034674/871951444895700 9290034675/871951444897100 | Model Number/(Short) EOC wcode 9290034676/871951444899500 9290034677/871951444901500 |
| Without igniter | n.a. | n.a. | n.a. | | | | |
| Philips | SN58 | 9136195799 9137001349 9137001348 9137100105 9136195199 | semi-parallel | | | | |
| | | 9137006553 9137006554 | semi-parallel | | | | |
| Vossloh Schwabe | Z250s | 140425 | series | | | | |
| | Z400s | 140427 | series | | | | |
| | Z400MK | 142897 | series | | | | |
| | PZI1000/1K | 140617 | parallel | | | | |
| Tridonic | ZRM-2.5-ES/CT | 87500086 | series | | | | |
| BAG | NI 400 LE 4K | 10007322 | series | | | | |
| | NP603 | 10067389 | parallel | | | | |
| PARMAR | PAE40 0255 | PAE400255 | series | | | | |
| | PXE07 0255 | | series | | | | |
| ELT | AVS 400-D | 3210232 | series | | | | |
| Electrostart | ZX400-T | 78.02.400.0-T | series | | | | |
| Magnetek (May & Christe) | ZG4.5 | | series | | | | |

MASTER LED SON-T - InstantFit

| | | |
|------------|--------------------------------------|---|
| 9290034670 | MAS LED SON-T IF 3.6Klm 23W 727 E27 |  |
| 9290034671 | MAS LED SON-T IF 4Klm 23W 740 E27 | |
| 9290034672 | MAS LED SON-T IF 5.4Klm 34W 727 E27 | |
| 9290034673 | MAS LED SON-T IF 6Klm 34W 740 E27 | |
| 9290034674 | MAS LED SON-T IF 8.1Klm 50W 727 E40 | |
| 9290034675 | MAS LED SON-T IF 9Klm 50W 740 E40 | |
| 9290034676 | MAS LED SON-T IF 10.8Klm 65W 727 E40 | |
| 9290034677 | MAS LED SON-T IF 12Klm 65W 740 E40 | |

Ballast - Igniter compatibility list

| | | |
|------|----------------------------|---|
| Key | | <i>This document is for information purposes and must be treated as recommendation. Signify attempts to provide accurate result which are generated in lab conditions and might not completely reflect actual conditions.</i> |
| | Compatible. | |
| | Limited compatibility | |
| | Not Compatible | |
| N.A. | Combination not applicable | |

| BSN-series ballast type (or similar) combined with following igniter | | | | MAS LED SON-T IF 3.6Klm 23W E27 | MAS LED SON-T IF 5.4Klm 34W E27 | MAS LED SON-T IF 8.1Klm 50W E40 | MAS LED SON-T IF 10.8Klm 65W E40 |
|--|---------------|---------------|----------|---------------------------------|---------------------------------|---------------------------------|----------------------------------|
| Brand | Type | art.nr | mode | Model Number/(Short) EOC wcode | Model Number/(Short) EOC wcode | Model Number/(Short) EOC wcode | Model Number/(Short) EOC wcode |
| Without igniter | n.a. | n.a. | n.a. | 9290034670/871951444887200 | 9290034672/871951444891900 | 9290034674/871951444895700 | 9290034676/871951444899500 |
| Philips | SI51 | 9136195199 | parallel | 9290034671/871951444889600 | 9290034673/871951444893300 | 9290034675/871951444897100 | 9290034677/871951444901500 |
| Vossloh Schwabe | Z250s | 140425 | series | | | | |
| | Z400s | 140427 | series | | | | |
| | Z400MK | 142897 | series | | | | |
| | PZI1000/1K | 140617 | parallel | | | | |
| Tridonic | ZRM-2.5-ES/CT | 87500086 | series | | | | |
| BAG | NI 400 LE 4K | 10007322 | series | | | | |
| | NP603 | 10067389 | parallel | | | | |
| PARMAR | PAE400255 | PAE400255 | series | | | | |
| | PXE07 0255 | | series | | | | |
| ELT | AVS 400-D | 3210232 | series | | | | |
| Electrostart | ZX400-T | 78.02.400.0-T | series | | | | |
| Magnetek (May & Christe) | ZG 4.5 | | series | | | | |

- Note**
- For enabling compatibility, the “Igniter comfort logic” function is equipped to simulate the low light level at start up of HID lamps, which in some cases can be observed as a short reduction of the light output of the lamp.
 - In rare cases the igniter comfort logic cannot stop the igniter. This is visible as continuously flicker of the light. Signify advises to remove/disconnect the igniter.
 - Instant ON/OFF – does not require to warm up or to cool down before restart.
 - The compatibility of the lamp with the gear is measured in the laboratory at nominal voltage (230VAC). The performance in real applications can be different.
 - Manufacturers of ballasts and igniters can change the technical design of their product without informing LED lamp suppliers. These changes can influence the performance of LED products. Signify cannot be held responsible for inaccuracies in the compatibility lists due to technical changes in ballasts or igniters.

Disclaimer:
Philips will not accept claims for any damage caused by implementing the recommendations in this document. More information:

[TrueForce LED Public \(Road – SON\) | 7165342 | Philips lighting](#)
[Installer Hub | Philips lighting](#)

MASTER LED SON - T - EM/Mains Voltage

| | | |
|------------|--------------------------------------|---|
| 9290034678 | MAS LED SON-T EM 3.6Klm 23W 727 E27 |  |
| 9290034679 | MAS LED SON-T EM 4Klm 23W 740 E27 | |
| 9290034681 | MAS LED SON-T EM 5.4Klm 34W 727 E27 | |
| 9290034682 | MAS LED SON-T EM 6Klm 34W 740 E27 | |
| 9290034684 | MAS LED SON-T EM 8.1Klm 50W 727 E40 | |
| 9290034685 | MAS LED SON-T EM 9Klm 50W 740 E40 | |
| 9290034687 | MAS LED SON-T EM 10.8Klm 65W 727 E40 | |
| 9290034688 | MAS LED SON-T EM 12Klm 65W 740 E40 | |

Ballast - Igniter compatibility list

| | | |
|------|----------------------------|---|
| Key | | <i>This document is for information purposes and must be treated as recommendation. Signify attempts to provide accurate result which are generated in lab conditions and might not completely reflect actual conditions.</i> |
| | Compatible. | |
| | Limited compatibility | |
| | Not Compatible | |
| N.A. | Combination not applicable | |

| | MAS LED SON-T EM 3.6Klm 23W E27 | MAS LED SON-T EM 5.4Klm 34W E27 | MAS LED SON-T EM 8.1Klm 50W E40 | MAS LED SON-T EM 10.8Klm 65W E40 |
|-----------------------------|---|---|---|---|
| EM ballast type | Model Number/(Short) EOC code 9290034678/871951444903900 9290034679/871951444905300 | Model Number/(Short) EOC code 9290034681/871951444909100 9290034682/871951444911400 | Model Number/(Short) EOC code 9290034684/871951444915200 9290034685/871951444917600 | Model Number/(Short) EOC code 9290034687/871951444921300 9290034688/871951444923700 |
| BSN 50W | | | | |
| BSN 70W | | | | |
| BHL 80W | | | | |
| BHL 125W | | | | |
| BSN 100W | | | | |
| BSN 150W | | | | |
| BSN 250W | | | | |
| BHL 250W | | | | |
| Direct Mains/Bypass Ballast | | | | |
| BSD 100L 406TS | | | | |
| BSD 150L 406TS | | | | |


The product is compatible with BSN and BHL ballast (or similar models from other suppliers), see above table.
The product is NOT compatible with electronic ballasts
The product is NOT compatible with CWA type of ballasts/transformers

Note

- The lamp is not compatible with any igniter. Ignitor should be removed.
- To get a decent PF, the power factor compensation capacitor should be removed.
- Instant ON/OFF – does not require to warm up or to cool down before restart.
- The compatibilty of the lamp with the gear is measured in the laboratory at nominal voltage (230VAC). The performance in real applications can be different
- Manufacturers of ballasts can change the technical design of their product without informing LED lamp suppliers. These changes can influence the performance of LED products. Signify cannot be held responsible for inaccuracies in the compatibility lists due to technical changes in ballasts.

Disclaimer:
Philips will not accept claims for any damage caused by implementing the recommendations in this document. More information:
[TrueForce LED Public \(Road – SON\) | 7165342 | Philips lighting](#)
[Installer Hub | Philips lighting](#)

MASTER LED SON-T Ultra Efficient - Mains

| | | |
|------------|---|---|
| 9290036771 | MAS LED SON-T UE M 3.6Klm 19W 727 E27 |  |
| 9290036772 | MAS LED SON-T UE M 4Klm 19W 740 E27 | |
| 9290036773 | MAS LED SON-T UE M 5.4Klm 28.5W 727 E27 | |
| 9290036774 | MAS LED SON-T UE M 6Klm 28.5W 740 E27 | |
| 9290036775 | MAS LED SON-T UE M 8Klm 42.8W 727 E40 | |
| 9290036776 | MAS LED SON-T UE M 9Klm 42.8W 740 E40 | |

Ballast - Igniter compatibility list

| | | |
|------|----------------------------|---|
| Key | | <i>This document is for information purposes and must be treated as recommendation. Signify attempts to provide accurate result which are generated in lab conditions and might not completely reflect actual conditions.</i> |
| | Compatible. | |
| | Limited compatibility | |
| | Not Compatible | |
| N.A. | Combination not applicable | |

| | | | |
|-----------------|---|---|---|
| EM ballast type | MAS LED SON-T UE M 3.6Klm 19W E27 | MAS LED SON-T UE M 5.4Klm 28.5W E27 | MAS LED SON-T UE M 8Klm 42.8W E40 |
| | Model Number/(Short) EOC code 9290036771/872016937419500 9290036772/872016937421800 | Model Number/(Short) EOC code 9290036773/872016937423200 9290036774/872016937425600 | Model Number/(Short) EOC code 9290036775/872016924037700 9290036776/872016924039100 |
| | Direct Mains/ Bypass Ballast | | |
| EM ballast | | | |


The product is NOT compatible with all types of ballasts/transformers

Note

- The lamp is not compatible with any Ballast Gear, ballast/igniter/power factor compensation capacitor should be removed.
- Instant ON/OFF – does not require to warm up or to cool down before restart.

Disclaimer:
Philips will not accept claims for any damage caused by implementing the recommendations in this document. More information:
[MASTER LED SON-T Ultra Efficient - Mains](#)
[Installer Hub | Philips Lighting](#)

TrueForce Core LED SON-T - Mains Voltage

| | | |
|------------|-------------------------------------|---|
| 9290043411 | TForce Core LED road 20W 722 E27 MV |  |
| 9290043412 | TForce Core LED road 26W 727 E27 MV | |
| 9290043413 | TForce Core LED road 26W 730 E27 MV | |
| 9290043414 | TForce Core LED road 26W 740 E27 MV | |
| 9290043415 | TForce Core LED road 32W 722 E40 MV | |
| 9290037308 | TForce Core LED road 17W 727 E27 MV | |
| 9290024848 | TForce Core LED road 17W 730 E27 MV | |
| 9290024849 | TForce Core LED road 17W 740 E27 MV | |
| 9290037310 | TForce Core LED road 40W 727 E40 MV | |
| 9290024852 | TForce Core LED road 40W 730 E40 MV | |
| 9290024853 | TForce Core LED road 40W 740 E40 MV | |
| 9290037756 | TForce Core LED road 45W 727 E40 MV | |
| 9290037788 | TForce Core LED road 45W 730 E40 MV | |
| 9290037757 | TForce Core LED road 49W 740 E40 MV | |

Ballast - Igniter compatibility list

| Key | | |
|------|----------------------------|--|
| | Compatible. | This document is for information purposes and must be treated as recommendation. Signify attempts to provide accurate result which are generated in lab conditions and might not completely reflect actual conditions. |
| | Limited compatibility | |
| | Not Compatible | |
| N.A. | Combination not applicable | |

| EM ballast type | TForce Core LED road 17W E27 | TForce Core LED road 26W E27 | TForce Core LED road 40W E40 | TForce Core LED road 45/49W E40 | TForce Core LED road 20W 722 E27 | TForce Core LED road 32W 722 E40 |
|------------------------------|-------------------------------|-------------------------------|-------------------------------|---------------------------------|----------------------------------|----------------------------------|
| | Model Number/(Short) EOC code | Model Number/(Short) EOC code | Model Number/(Short) EOC code | Model Number/(Short) EOC code | Model Number/(Short) EOC code | Model Number/(Short) EOC code |
| | 9290037308/872016926771800 | 9290043412/872110312934500 | 9290037310/872016926775600 | 9290037756/872016929743200 | 9290043411/872110312932100 | 9290043415/872110312940600 |
| | 9290024848/871951431625600 | 9290043413/872110312936900 | 9290024852/871951431633100 | 9290037788/872016929747000 | | |
| Direct Mains/ Bypass Ballast | | | | | | |
| EM ballast | | | | | | |

The product is NOT compatible with all types of ballasts/transformers

Note

- The lamp is not compatible with any Ballast Gear, ballast/igniter/power factor compensation capacitor should be removed.
- Instant ON/OFF – does not require to warm up or to cool down before restart.

Disclaimer:

Philips will not accept claims for any damage caused by implementing the recommendations in this document. More information:

[Trueforce Core LED SON-T | 8852552 | Philips lighting](#)

[Installer Hub | Philips lighting](#)

TrueForce LED HPL - EM/Mains

| | | |
|------------|----------------------------------|---|
| 9290020061 | TForce LED HPL ND 28-21W E27 830 |  |
| 9290020062 | TForce LED HPL ND 30-21W E27 840 | |
| 9290020063 | TForce LED HPL ND 38-28W E27 830 | |
| 9290020064 | TForce LED HPL ND 40-28W E27 840 | |
| 9290020065 | TForce LED HPL ND 57-42W E27 830 | |
| 9290020066 | TForce LED HPL ND 60-42W E27 840 | |
| 9290020067 | TForce LED HPL ND 57-42W E40 830 | |
| 9290020068 | TForce LED HPL ND 60-42W E40 840 | |

Ballast - Igniter compatibility list

| | | | |
|------|----------------------------|--|--|
| Key | | | This document is for information purposes and must be treated as recommendation. Signify attempts to provide accurate result which are generated in lab conditions and might not completely reflect actual conditions. |
| | Compatible. | | |
| | Limited compatibility | | |
| | Not Compatible | | |
| N.A. | Combination not applicable | | |

| EM ballast type | TForce LED HPL ND 21W E27 | TForce LED HPL ND 28W E27 | TForce LED HPL ND 42W E27 | TForce LED HPL ND 42W E40 |
|------------------------------|---|---|---|---|
| | Model Number/(Short) EOC code 9290020061/871869963814600 9290020062/871869963816000 | Model Number/(Short) EOC code 9290020063/871869963818400 9290020064/871869963820700 | Model Number/(Short) EOC code 9290020065/871869963822100 9290020066/871869963824500 | Model Number/(Short) EOC code 9290020067/871869963826900 9290020068/871869963828300 |
| BSN 50W | | | | |
| BSN 70W | | | | |
| BHL 80W | | | | |
| BHL 125W | | | | |
| BSN 100W | | | | |
| BSN 150W | | | | |
| BSN 250W | | | | |
| BHL 250W | | | | |
| Direct Mains/ Bypass Ballast | | | | |

The product is compatible with BSN and BHL ballast (or similar models from other suppliers), see above table.
The product is NOT compatible with electronic ballasts
The product is NOT compatible with CWA type of ballasts/transformers

- Note
- The lamp is not compatible with any igniter. Ignitor should be removed.
 - To get a decent PF, the power factor compensation capacitor should be removed.
 - Instant ON/OFF – does not require to warm up or to cool down before restart.
 - The compatibilty of the lamp with the gear is measured in the laboratory at nominal voltage (230VAC). The performance in real applications can be different
 - Manufacturers of ballasts can change the technical design of their product without informing LED lamp suppliers. These changes can influence the performance of LED products. Signify cannot be held responsible for inaccuracies in the compatibility lists due to technical changes in ballasts.

Disclaimer:
Philips will not accept claims for any damage caused by implementing the recommendations in this document. More information:

[TrueForce LED Public \(Urban/Road – HPL/SON\) | 5763385 | Philips lighting](#)
[Installer Hub | Philips lighting](#)

MASTER LED HPL - Mains

| | | |
|--------------|---|---|
| 929003530702 | MAS LED HPL M 2.8Klm 19W 830E27 FR G |  |
| 929003530802 | MAS LED HPL M 3Klm 19W 840 E27 FR G | |
| 929003530902 | MAS LED HPL M 3.8Klm 24W 830 E27 FR G | |
| 929003531002 | MAS LED HPL M 4Klm 24W 840 E27 FR G | |
| 929003531102 | MAS LED HPL M 5.6Klm 33.5W 830 E27 FR G | |
| 929003531202 | MAS LED HPL M 6Klm 33.5W 840 E27 FR G | |
| 929003531302 | MAS LED HPL M 5.6Klm 33.5W 830 E40 FR G | |
| 929003531402 | MAS LED HPL M 6Klm 33.5W 840 E40 FR G | |

Ballast - Igniter compatibility list

| | | |
|------|----------------------------|---|
| Key | | <i>This document is for information purposes and must be treated as recommendation. Signify attempts to provide accurate result which are generated in lab conditions and might not completely reflect actual conditions.</i> |
| | Compatible. | |
| | Limited compatibility | |
| | Not Compatible | |
| N.A. | Combination not applicable | |

| | | | | |
|-----------------|---|---|---|---|
| EM ballast type | MAS LED HPL M 2.8Klm 19W E27 | MAS LED HPL M 3.8Klm 24W E27 | MAS LED HPL M 5.6Klm 33.5W E27 | MAS LED HPL M 5.6Klm 33.5W E40 |
| | Model Number/(Short) EOC code 9290035307/871951445193300 9290035308/871951445195700 | Model Number/(Short) EOC code 9290035309/871951445197100 9290035310/871951445199500 | Model Number/(Short) EOC code 9290035311/871951445201500 9290035312/871951445203900 | Model Number/(Short) EOC code 9290035313/871951445205300 9290035314/871951445207700 |
| | Direct Mains/ Bypass Ballast | | | |
| EM ballast | | | | |

The product is NOT compatible with all types of ballasts/transformers

Note

- The lamp is not compatible with any Ballast Gear, ballast/igniter/power factor compensation capacitor should be removed.
- Instant ON/OFF – does not require to warm up or to cool down before restart.

Disclaimer:

Philips will not accept claims for any damage caused by implementing the recommendations in this document. More information:

[CorePro LED HPI - Mains](#)

[Installer Hub | Philips lighting](#)

TrueForce CorePro LED HPL - Mains Voltage

| | | |
|------------|--------------------------------------|---|
| 9290023497 | TForce Core LED HPL 13W E27 830 FR |  |
| 9290023498 | TForce Core LED HPL 13W E27 840 FR | |
| 9290023499 | TForce Core LED HPL 18W E27 830 FR | |
| 9290023500 | TForce Core LED HPL 18W E27 840 FR | |
| 9290038365 | TForce Core LED HPL 24.5W E27 830 FR | |
| 9290038366 | TForce Core LED HPL 24.5W E27 840 FR | |
| 9290024812 | TForce Core LED HPL 36W E27 830 FR | |
| 9290024813 | TForce Core LED HPL 36W E27 840 FR | |
| 9290024814 | TForce Core LED HPL 36W E40 830 FR | |
| 9290024815 | TForce Core LED HPL 36W E40 840 FR | |
| 9290037311 | TForce Core LED HPL 13W E27 827 FR | |
| 9290037312 | TForce Core LED HPL 18W E27 827 FR | |
| 9290037313 | TForce Core LED HPL 26W E27 827 FR | |
| 9290037314 | TForce Core LED HPL 36W E27 827 FR | |
| 9290037315 | TForce Core LED HPL 36W E40 827 FR | |

Ballast - Igniter compatibility list

| | | |
|------|----------------------------|---|
| | Compatible. | <i>This document is for information purposes and must be treated as recommendation. Signify attempts to provide accurate result which are generated in lab conditions and might not completely reflect actual conditions.</i> |
| | Limited compatibility | |
| | Not Compatible | |
| N.A. | Combination not applicable | |

| | | | | | |
|-----------------|---|---|---|---|---|
| EM ballast type | TForce Core LED HPL 13W E27 | TForce Core LED HPL 18W E27 | TForce Core LED HPL 24.5W E27 | TForce Core LED HPL 36W E27 | TForce Core LED HPL 36W E40 |
| | Model Number/(Short) EOC code 9290037311/872016926777000 9290023497/871869975025100 9290023498/871869975027500 | Model Number/(Short) EOC code 9290037312/872016926779400 9290023499/871869975029900 9290023500/871869975031200 | Model Number/(Short) EOC code 9290038364/872110314385300 9290038365/872016933633900 9290038366/872016933635300 | Model Number/(Short) EOC code 9290037314/872016926783100 9290024812/871951429927600 9290024813/871951429929000 | Model Number/(Short) EOC code 9290037315/872016926785500 9290024814/871951429931300 9290024815/871951429933700 |
| | Direct Mains/ Bypass Ballast | | | | |
| | EM ballast | | | | |

The product is NOT compatible with all types of ballasts/transformers

Note

- The lamp is not compatible with any Ballast Gear, ballast/igniter/power factor compensation capacitor should be removed.
- Instant ON/OFF – does not require to warm up or to cool down before restart.

Disclaimer:

Philips will not accept claims for any damage caused by implementing the recommendations in this document. More information:

[Trueforce CorePro LED HPL | 7903997 | Philips lighting](#)
[Installer Hub | Philips lighting](#)

